

# LIFT OFF

- Fast acting cleaner/polish stripper
- For heavy duty cleaning of safety flooring
- Helps in removal of oleo-resinous finishes

## Product Information

### DESCRIPTION:

Lift Off is a powerful blend of alkalis, sequestrant, wetting agents and degreasing solvent, designed for the removal of metallised and non-metallised emulsion polishes. Lift Off can also be used for heavy duty cleaning of safety flooring and to help in the removal of oleo-resinous finish build-up and some adhesive residues.

Lift Off is suitable for use on sealed/coated wood and composition, vinyl, thermoplastic and stone surfaces. Care should be taken on linoleum floors to avoid prolonged contact, which may cause damage to the surface. Product must not be used on unsealed/uncoated wood floors.

### INSTRUCTIONS:

Ensure good ventilation at all times during application.

**REMOVAL OF FLOOR POLISHES:** Dilute 1:10 in warm water and apply to a workable section (approx. 8—10m<sup>2</sup>). Apply liberally, (avoiding excess to edges of wooden floors), and allow approximately 10 minutes contact time, ensuring the surface remains wet at all times. Machine scrub the floor using a rotary scrubbing machine fitted with either a black or green floor pad, dependent on the level of abrasion required. Remove all slurry immediately using a suitable wet pick-up machine. When completed, the surface should be rinsed twice with clean water to completely remove any residues. It is recommended that the floor be then wet vacuumed again and allowed to dry thoroughly prior to polish application.

**CLEANING OF SAFETY FLOORING:** Dilute product 1:20 and use in the same method as above, using a green floor maintenance pad or polypropylene scrubbing brush on the machine. For the removal of black heel marks, apply neat and allow to stand for 10—15 minutes before normal scrubbing procedure takes place.

**REMOVAL OF OLEO-RESINOUS FINISH BUILD-UP:** Apply Lift Off neat and allow to stand for approximately 10—15 mins. Apply hot water, allow 5 minutes then remove residual slurry using a good quality scraper. Rinse at least twice with clean water and allow to dry.

**PRECAUTIONS:** Use warm water only—temperature must not exceed 60°C.

**STORAGE:** Store in a cool, dry place. Protect from frost. Keep out of the reach of children.

**HEALTH AND SAFETY:** For full health and safety information, please refer to the product Material Safety Data Sheet.

*The information provided herein is correct to the best of our knowledge. No liability for any errors or omissions is accepted. You should satisfy yourself by appropriate trials that the product is suitable for the intended use. Granwax Products Ltd can accept no responsibility for any loss as a result of any person placing reliance on any material contained herein.*

*This revision Dec.2012*



## GRANWAX

Products Limited

Installation, Finishing & Maintenance Systems  
for wood and Sports Floors

West Street,  
Riddings,  
Alfreton,  
Derbyshire DE55 4EW  
Tel: 01773 541177  
Fax: 01773 541429  
email: [info@granwax.com](mailto:info@granwax.com)  
web: [www.granwax.com](http://www.granwax.com)