

MATERIAL SAFETY DATA SHEET



Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: September 2009

Reviewed by MC

1. Identification of substance

Substance: **MS Flex Wood Floor Adhesive** Supplier: Granwax Products Limited
West Street
Riddings, Alfreton
Derbyshire DE55 4EW
Telephone: 01773 541177 Fax: 01773 541429
This revision: June 2009

2. Composition/Data on components

Composition and classification of potentially hazardous components.

<u>Component</u>	<u>Concentration range</u>	<u>Classification</u>	<u>Risk Phrase</u>
Di isononylphthalates 28553-12-0	2.5 – 10%		

3. Hazards identification

None applicable

MATERIAL SAFETY DATA SHEET



Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: June 2009

Reviewed by MC

4. First aid measures

Skin exposure: immediately wash the affected area with soap or mild detergent and water. Remove contaminated clothing. If symptoms persist seek medical advice.

Eye splashes: If the material is splashed into the eye, wash the affected eye with clean running water for at least 15 minutes. Seek medical advice.

Swallowing (ingestion): If material is accidentally swallowed, do not make patient vomit, seek medical advice. This information should be taken with the patient when seeking medical advice.

Inhalation; Move patient to fresh air. If patient is unconscious, place in the recovery position and seek medical help immediately. Do not give patient anything to drink.

CALL FOR MEDICAL ASSISTANCE IF YOU FEEL UNWELL

5. Fire fighting measures

CO2 or foam extinguishants

No special requirements.

6. Accidental release measures

Spillages should be contained with a non-combustible absorbent material and collected for disposal in accordance with the local regulations.

Spillages should not be allowed to run to surface waters . PPE must be worn.

7. Handling & storage

No special requirements

All chemical preparations should be stored securely where they cannot be interfered with or used by unauthorised persons.



GRANWAX
Products Limited

MATERIAL SAFETY DATA SHEET

Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: June 2009

Reviewed by MC

Exposure controls & personal protection

No special requirements

9. Physical and chemical properties

Appearance:	Pasty beige	Odour	Characteristic
pH:	Not Applicable	Boiling point / range:	NA
Melting point / range	Undetermined	Flash point:	NA
Flammability	Non Flammable	Autoflammability:	Not applicable
Explosive properties	Not applicable	Oxidising properties:	none
Vapour pressure	Not applicable	Relative density:	Approx. 1.55g/cm ³
Solubility	not miscible	Partition coefficient: n-octanol / water	Not determined
Solvent Content	0%	Solids Content	60%

10. Stability and reactivity

Product generally stable

11. Toxicological information

This product is of generally low toxicity

12. Ecological information

Class WKG1 Slight water hazard.

13. Disposal considerations

This product is not classified as Harmful/Flammable. Any surplus or waste arising from the normal use of this product must be disposed of in accordance with the local waste regulations.

MATERIAL SAFETY DATA SHEET



Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: June 2009

14. Transport information

Not classified as a hazard

15. Regulatory information

None

16. Other information

No other safety information is applicable to the use of this preparation for its intended purpose