

SUPREME NATURAL BASE

Water based coloured base coat



GRANWAX
Limited

Installation, Finishing & Maintenance Systems
for Wood and Sports Floors

DESCRIPTION

Granwax Supreme Natural Base is formulated to act as a fast drying coloured base coat for new or refurbished wood flooring that has been sanded, prior to the application of the chosen Granwax water based floor finish. It is ideal for use on strip, block or mosaic wood flooring that has no previous history of residual wax.

Important: **Granwax Supreme Natural Base** cannot be used as a base coat on reclaimed timber floors with unknown history of previous applications or on floors potentially contaminated with traditional wax deposits. **Granwax Supreme Natural Base** cannot be used as a final floor finish, nor should it be used in conjunction with oil or solvent based finishes. Do not use **Granwax Supreme Natural Base** on floors that have been already stained or coloured.

Please contact our technical department, your local representative or product supplier if you have any questions regarding preparation, application or require advice before commencing work.



PREPARATION

It is important that operatives are conversant with all aspects of procedures prior to commencing work. Please note that any grit grades are offered as a guide only and operatives must ensure that grit grades used are suitable for the particular project and that a sufficient key is created to enable good adhesion of the coats of the chosen Granwax water based finish.

Ensure adequate ventilation on site at all times throughout all procedures. Recommended site conditions are 20°C/50% R.H.

Ideally, floors should be final sanded with fine grit sandpaper, eg. 100-120grit. Any remaining lines to be removed with appropriate sandscreen disc or finishing sander. Thoroughly remove dust and debris by vacuum and tack rag method.



THE PRODUCT

- ✓ Available sizes: 5 litres only
- ✓ Fast drying - approximately 1 hour
- ✓ Easy to apply
- ✓ Low odour

PROUDLY MADE IN THE UK



TECHNICAL INFORMATION

COVERAGE

10-12m² per litre. This coverage rate is offered as a guide only as surface porosity and type of application will affect coverage rates. Pack size - 5 litre and 2.5litre containers.

DRYING TIME

Approximately 1 hour (at 20°C/50% R.H.). Please note that poor ventilation, low temperature and/or high humidity will all extend or affect product drying times.

STORAGE

Avoid storing in extreme hot or cold temperatures. Ideally, store between 10°C and 30°C. Protect from frost.

SHELF LIFE

Please refer to 'Use by' date on top of container. For best results, opened containers should be used immediately.

HEALTH & SAFETY

For product health and safety information, please refer to our Material Safety Data Sheet.

**Please note that drying and curing times will be extended or reduced dependent on site conditions. In some circumstances this may affect the overall appearance if not properly addressed.*

The information provided herein is correct to the best of our knowledge. No liability for any errors or omissions is accepted. Granwax Limited can accept no responsibility or liability for any loss as a result of any person placing reliance on any information contained herein nor for any loss or damage arising from the use of this product if used in areas subjected to severe abrasion, i.e. broken glass or impact damage. Prospective users should therefore satisfy themselves by appropriate trials that the product is suitable for the intended purpose.

This revision July 2024.

APPLICATION

Ensure site is properly ventilated and dust free at all times during product application. Product should not be applied in room temperatures below 10°C or above 30°C, and relative humidity must remain below 85%, otherwise the quality and performance of the product will be affected. If any doubt exists regarding site conditions or the procedure, please contact our technical department or your Granwax representative before commencing work.

Please note: One coat or two coats of **Granwax Supreme Natural Base** can be applied depending on preference. Two coats will increase depth of colour. To ensure desired results, it is recommended that tests be carried out prior to full use of the product. If two coats are required, apply second coat after first coat is dry (approximately 1 hour). Prior to second coat application, floor may need to be lightly abraded to remove any raised grain.

Granwax Supreme Natural Base can be applied using a Granwax Applicator and pad, a Granwax Microfibre Roller or a Padco T-Bar Coater with blue foam sleeve. The size of the floor area, together with the time allowed for coating will determine the type of applicator to be used. For small or awkward areas a good quality brush should be used. Apply evenly, working with the grain of wood where possible.

Certain timbers may require light abrasion prior to receiving top coats of the chosen Granwax water-based floor finish. This can be carried out using rotary machine fitted with an appropriate sandscreen disc or Magic Pad (this choice will be dependent on the hardness of the product).

Overcoating with the chosen Granwax waterbased finish can take place after approximately 1-2 hours.



GRANWAX
Limited



Part of the ISF Group Limited

West Street • Riddings • Alfreton • Derbyshire • DE55 4EW

Telephone: 01773 541177 • Email: info@granwax.com • www.granwax.com

Installation, Finishing & Maintenance Systems for Wood and Sports Floors