



## Maintenance Schedule for GRANWOOD in non-sporting activity areas

Following the guidance below and using only the recommended Granwax cleaning and maintenance products on Granwood floors will ensure the longevity and suitability for purpose of your Granwood floor.

The recommended Granwax emulsion floor dressings and maintenance products are:

**ACRYLIC** - Specifically for use on areas of normal traffic, e.g. assembly rooms, classrooms, offices, etc.

**TUFSHEEN 25** - For use on areas of heavy concentrated traffic areas, e.g. corridors, main entrances, etc.

**SPEEDKLEEN** - For spray cleaning/buffing with rotary floor machine

**JADEX** - For regular floor cleaning, mopping and spot cleaning

### Initial Treatment

In order to prevent dirt, abrasive materials and moisture being carried onto the floor, entrance areas should be fitted with appropriate dirt control matting.

Once the new Granstone has fully cured (normally minimum of 7 days), it is suggested that two thin coats of **Acrylic or Tufsheen 25** dressings (polish) are applied to the floor if required, which will enhance the overall appearance and offer further protection to the surface. The dressing should be applied to a clean, dry and lightly abraded surface.

PLEASE NOTE: POLISH/DRESSING OR POLYMER BASED MAINTAINERS SHOULD NOT BE USED ON FLOORS WHERE ANY SPORTING ACTIVITIES TAKE PLACE

### Daily Maintenance

Sweep the floor daily using a "V" mop sweeper, push mop or broom to collect dirt and other abrasive materials. Entrance matting should also be cleaned and vacuumed regularly. The use of sweeping compounds should be avoided. It is very important that all efforts are made to remove abrasive material to minimise scratching and premature wear of the finish.

### Frequent Maintenance

When necessary, damp mop the floor using a warm water solution of **Jadex** neutral detergent or, alternatively, **Speedkleen** for spray cleaning/buffing. Please refer to the relevant product data sheet for dilution rates, etc.

Care should be taken that excess moisture is not allowed to remain in contact with the floor surface for prolonged periods. The use of a wet vacuum machine is recommended to minimise the possible risk of slip on a wet surface. A scrubber/dryer machine is recommended for large areas.

Any spillage on the floor should be quickly removed using absorbent cloth and then damp-mopped with **Jadex** or **Speedkleen**.

### Periodic Maintenance

It will be necessary to apply further coats of dressing (polish) in worn areas. Apply chosen dressing to clean surface as previously. After a period of time, your floor will require recoating with Granstone (manufactured by Granwax) in order to restore the original appearance as much as possible and offer protection to the surface. Please refer to the relevant Granwood floor recoating procedure instructions before undertaking this work. Alternatively, you may contact us for specialist advice or obtain a quote for refurbishment work by Granwood Contracts Department.

The Granwax recommended coating system materials are:

**GRANSTONE** - For floors where a moisture cured one-pack polyurethane has been used previously and which are subject to very heavy traffic.

**GRANSEAL** or **GRANSEAL HEAVY DUTY** - For floors where an oleo resinous type of finish has been used previously.

**Machine Cleaning:**

Should be carried out using preferred Granwax product for periodical removal of dirt and polish build-up

**Aftercare Advice:**

Granwax offer a free aftercare, cleaning and technical advisory service for all floors maintained with Granwax care and maintenance products. Advice and demonstrations of our products and machinery are available upon request. Please contact your local representative or our office.

**Floor Essentials:**

Granwax supply a full range of specialist binding primers, seals and finishes, accessories, applicators, specialist floor maintenance products and dirt control matting systems.

For further advice or information please contact  
Granwax Sales Office 01773 541177  
Granwax Website – [www.granwax.com](http://www.granwax.com)  
Email – [info@granwax.com](mailto:info@granwax.com)

Granwax constantly strive to improve their product performance relating to floor care and, as such, reserve the right to vary product specification and/or recommendations without prior notice.

Granwax warrants that the products described in this literature are of merchantable quality and are fit for the purpose intended provided that the instructions relating to storage, handling, preparation and usage are observed.

Maintenance Schedule for Granwood floors in non-sporting activity areas  
*This data sheet supersedes previous issues  
September 2015*

**GRANWAX PRODUCTS LIMITED  
WEST STREET  
RIDDINGS  
ALFRETON  
DERBYS  
DE55 4EW**